

NON-METALLIC POLYESTER GRP LATCH & HINGE TYPE

Features

- IP66
- Polyester GRP construction
- Grey and clear door options
- Self extinguishing
- UV stabilised
- IK08 impact resistant
- -40 degrees - 120 degrees celsius
- Door hinges 180 degree opening
- Complete with wall mounting bracket (4 pcs / set)
- RAL 7035
- ANSI/IEC 60529-2004



Typical Applications



Grey Door Hinged GRP Enclosure Selection Table

Model No.	Dimensions (mm)		
	Height	Width	Depth
PNTIP325	300	250	140
PNTIP43	400	300	200
PNTIP44	400	400	200
PNTIP54	500	400	200
PNTIP64	600	400	230
PNTIP65	600	500	230
PNTIP86	800	600	300

Clear Window Hinged GRP Enclosure Selection Table

Model No.	Dimensions (mm)		
	Height	Width	Depth
PNTX325	300	250	140
PNTX43	400	300	200
PNTX44	400	400	200
PNTX54	500	400	200
PNTX64	600	400	230
PNTX65	600	500	230
PNTX86	800	600	300

Mounting Pans to Suit TIP & TX Enclosures

Model No.	Description
PN325	Metal Mounting Plate for TIP & TX Enclosures
PN430	Metal Mounting Plate for TIP & TX Enclosures
PN440	Metal Mounting Plate for TIP & TX Enclosures
PN540	Metal Mounting Plate for TIP & TX Enclosures
PN640	Metal Mounting Plate for TIP & TX Enclosures
PN650	Metal Mounting Plate for TIP & TX Enclosures
PN860	Metal Mounting Plate for TIP & TX Enclosures

Inner Doors to Suit TIP & TX Enclosures

Model No.	Description	Dimensions (mm)	
		Height	Width
PNTP43	Inner door to suit TIP & TX Enclosures	364	245
PNTP44	Inner door to suit TIP & TX Enclosures	364	345
PNTP54	Inner door to suit TIP & TX Enclosures	464	345
PNTP64	Inner door to suit TIP & TX Enclosures	564	345
PNTP65	Inner door to suit TIP & TX Enclosures	564	445
PNTP86	Inner door to suit TIP & TX Enclosures	764	545