

HARRIER EXTREME

LED HIGH & LOW BAYS



HARRIER EXTREME

The Harrier Extreme is a high efficacy LED High Bay Floodlight designed for Industrial and Indoor Lighting. It features a superior high output and a unique optical design that virtually eliminates glare with minimal impact on performance.



TYPICAL APPLICATIONS







Heavy Vehicle Workshops, MIA Infrastructure, Warehouses & Stores, General Workshops, Factories, Heavy Industry, Overhead Cranes, Airports

SPECIFICATIONS


Model:	PLIHEX60	PLIHEX100	PLIHEX150	PLIHEX200	PLIHEX240
Optical Characteristics					
Rated Wattage	60W	100W	150W	200W	240W
Lumens	10020	15800	24900	33200	39120
System Efficacy	167Lm/W	158Lm/W	166Lm/W	166Lm/W	163Lm/W
Colour Temperature CCT	5000K (5700K / 4000K / 3000K)				
Frequency	>70 (>80 Optional)				
Reported L70	> 50,000 Hours				
Lens Optic Type	60° / 90° / 120°				
Electrical Characteristics					
Input	100-277VAC (347/480V Optional)				
Frequency	50Hz				
Powerfactor	<0.96				
Total Harmonic Distortion	<20%				
Environment					
IP Rating	IP40	IP65			
Impact Rating	IK08				
Operating Temperature	-40°C To 50°C				
Product Material and Mounting					
Option 1	Eyebolt				
Option 2	U Bracket				
Product Material	Aluminum Housing				
Lens / Optics Material	Toughened Glass and PC Lens				
Dimensions and Weights					
Product Dimensions	Refer to dimensions below				
Product Weight		2.9KG			2KG
Packaging Dimensions		00*300	480*480*310		80*330
Gross Weight	3.8	KG	6.0KG	7.2	KG
Warranty and Certifications					
Warranty	5 Year Warranty				
Certifications		SAA / CE / RoHS			

 $^{^{\}ast\ast}$ High lumen output up to 170Lm/W available on request

LED HIGH & LOW BAYS




DIMENSIONS



А	В	С	D			
60W and 100W Models						
248mm	710mm	138mm	182mm			
150W Model						
319mm	710mm	138mm	183mm			
200W and 240W Models						
400mm	710mm	141mm	202mm			

PHOTOMETRIC DIAGRAMS





LED HIGH & LOW BAYS



ORDERING METHODOLOGY

240W

PLI-HEX

XXX WATTS CCT XX BEAM ANGLE

60W 100W 50 (5000K) 02 (90°)
150W 40 (4000K) 30 (3000K)

ACCESSORIES

EYEBOLT PLIHEX/EB
U BRACKET PLIHEX/UB
PE CELL PLIHEX/P
MOTION SENSOR PLIHEX/M
POLYCARBONATE DIFFUSER PLIHEX/PC







